



EF3^{PREMIUM}P

PREMIUM RAPID SETTING FLEXIBLE WHITE FLOOR AND WALL TILE ADHESIVE

1 UNIQUE IDENTIFICATION CODE	Eco Fusion Premium Rapid Setting – White
2 TYPE BATCH OR SERIAL NUMBER OR ANY OTHER ELEMENT ALLOWING IDENTIFICATION OF THE CONSTRUCTION PRODUCT AS REQUIRED BY ARTICLE 11(4)	See Product Packaging for batch number and production date.
3 INTENDED USES OF CONSTRUCTION PRODUCT, IN ACCORDANCE WITH APPLICABLE HARMONISED TECHNICAL SPECIFICATION AS FORESEEN BY THE MANUFACTURER	Genuine S1, ultra-low carbon, fast setting thin bed adhesive with increased adhesion and non-slip properties for use inside and outside.
4 NAME, REGISTERED NAME OR REGISTERED TRADE MARK AND CONTACT ADDRESS OF THE MANUFACTURER AS REQUIRED BY ARTICLE 11 (5)	Eco Fusion Limited, Coes Road, Dundalk Co Louth
5 NAME AND CONTACT ADDRESS OF THE AUTHORIZED REPRESENTATIVE WHOSE MANDATE COVERS THE TASK SPECIFIED IN ARTICLE 12 (2)	Not Applicable
6 ASSESSMENT AND VERIFICATION OF CONSTANCY OR PERFORMANCE	System 3 System 4 – for Reaction to Fire
7 NOTIFIED BODY	Not Applicable
8 EUROPEAN TECHNICAL ASSESSMENT	Not Applicable



9 DECLARED PERFORMANCE	EN 12004:2007
	CLASSIFICATION C2FS1
	REACTION TO FIRE Class E
	RELEASE OF CORROSIVE SUBSTANCE See SDS
	BOND STRENGTH + Early Tensile Adhesion Strength $\geq 0.5\text{N/mm}^2$ + Initial Tensile Adhesion Strength $\geq 1\text{N/mm}^2$
	DURABILITY FOR + Tensile Adhesion Strength After Heat Ageing $\geq 1\text{N/mm}^2$ + Tensile Adhesion Strength After Water Immersion $\geq 1\text{N/mm}^2$ + Tensile Adhesion Strength After Freeze/Thaw $\geq 1\text{N/mm}^2$
	TRANSVERSE DEFORMATION 2.5 mm

The Performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of Eco Fusion

CHRIS VICKERS
Technical Director

PLACE

DATE