

EFB

BUTYL TAPE

- + High Adhesive Strength Tape
- + Tear Resistant
- + Flexible
- + Good UV Resistance
- + Easy to Use
- + Soft Workability

ECO FUSION BUTYL TAPE

is a fleece coated, permanently elastic butyl sealing tape with a high adhesive strength and tear resistance. It can be used in corners and to cover joints in wet rooms, for fixing ridge tile flashing or membranes. It has excellent adhesion to a wide range of substrates.

The fleece coating allows an excellent combination with common sealants as polymer dispersions and mineral flexible sealing slurries and reaction resins.

For use as an air, dust or water seal for compression joints and seams, water sealing applications and for fixing ridge tile flashing or membranes.

SUBSTRATE PREPERATION

Will depend on the nature and form of the substrate and the sealing system to be used.

- + All surfaces must be clean, dry, sound, and free of any contaminants.
- + Remove dirt, oil, grease, or other separating agents.
- + A suitable Primer such as Eco Fusion Tilers Primer should be applied.

APPLICATION

Cut the sealing tape to the required length. Remove the first half of the back of the silicone strip and press firmly to the intended surface. Then remove the second silicone strip of the sealing tape and stick as far as possible with loop formation at the surface. The sealing strip must be positioned correctly at the first try. A correction is possible conditionally and depends on the substrate. For safety reasons the sealing strip must be replaced with a new section.

INFORMATION ON FURTHER PROCESSING

The tape ensures excellent compatibility and good adhesion with polymer dispersions, flexible mineral sealing slurries and reaction resins. However it is advisable to conduct a compatibility test before applying other products.

CONSUMPTION

When calculating consumption allow for a tape overlap of at least 5cms.

SUPPLIED AS

10m roll

CLEANING OF TOOLS AND EQUIPMENT

Rinse tools and dirtied areas with water immediately after use.

STORAGE

This product has a shelf life of 24 months if stored in its unopened packaging in normal dry conditions. Do not use below 5°C.

HEALTH AND SAFETY

For more information and precautions for use refer to safety data sheet.

The Information given in this technical sheet is given in good faith. Eco Fusion cannot accept liability for loss or damage caused by the incorrect use of its products or poor workmanship. The user must ensure the product's suitability for the application intended and if in doubt should seek written technical advice for the product's application.

TECHNICAL SUMMARY

| | |
|---------------------|--------|
| THICKNESS | 0.60mm |
| WIDTH | 75mm |
| WORKING TEMPERATURE | +5°C |